

Product Description

High quality wall paint with excellent coverage and low odour interior paint with excellent cleaning properties and resistant surface.

The product is suitable for most use in domestic houses, as living rooms and kitchens as well as in offices, where a matt, smooth and burnish resistant appearance is required.

Wet scrub Class 1, EN 13300, Emmisonstested M1 (EMCBM).

B&J 10 fulfills the requirements the EU Eco-label in all colours if tinted within the B&J tintingsystem Monicolor.

Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion. Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent. Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

This product has been qualified for the EU Eco-label by reducing the water and air pollution as well as the quantity of waste.

Further information on why this product was assigned with EU Eco-label can be found on www.ecolabel.eu

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

Technical data

Binder:	Acrylic
Type:	Acrylic wall paint
Gloss:	App. 6, matt
Vol. dry:	
Colours:	White, Off white, NCS-S 0500 and B&J tinting system
Drying:	App. 2-4 hours at 20° C. RH.: 65%. Recoateable after app. 8 hours.
Application:	+10 °C to + 25° C. RH: 40-80%
Thinning:	Water
Coverage:	8-10 m ² /ltr
Tools:	Brush, roller or airless
Mal-Code:	00-1 (1993)



